

TOPY-VP Middle Speed VFFS Packing Machine



Application

Loose solid material, such as puffy food, shrimp roll, peanut, popcorn, cornmeal, seed, sugar and salt etc. which shape is roll, slice and granule.

- PLC controller with touch screen interface
- Servo-driven end seal jaws
- Servo-driven film transport
- Hot printer and film feeding system synchronous
- Quickly changing one-piece bag former
- Eye mark sensor for film tracking
- Stainless steel frame

Specifications

Model	TOPY-VP420	TOPY-VP520	TOPY-VP620	TOPY-VP800
Bag Size	(L) 60-230mm* (W) 60-200mm	(L) 100-300mm* (W) 80-250mm	(L) 100-380mm* (W) 100-300mm	(L) 50-380mm* (W) 110-400mm
Bag Speed	15- 60bags/min	15- 60bags/min	15- 60bags/min	10-30bags/min
Film width	140-420mm	180-520mm	220-620mm	340-800mm
Air consumption	0.6Mps 0.36m ³ /min	0.6Mps 0.36m ³ /min	0.6Mps 0.4m ³ /min	0.6Mps 0.7m ³ /min
Power supply	2.2kw, 220V 50/60HZ	3.0kw, 220V 50/60HZ	4.0kw, 220V 50/60HZ	4.5kw, 220V 50/60HZ
Packed Dimensions	(L) 1430* (W) 970* (H) 1600mm	(L) 1550* (W) 1160* (H) 1480mm	(L) 1600* (W) 1260* (H) 1680mm	(L) 1600* (W) 1500* (H) 2050mm



TOP Y MACHINERY CO.,LTD

Filling Systems	Optional device
Fits most fillers for dry or liquid applications:	
- Auger fillers	- Air flushing system
- Cup fillers	- Nitrogen gas flushing
- Linear scales	- Gusset device
- Combination weighers	- Air expeller
- Combination scales	- Hole punch device
Packing material	- Tear notch device
- Heat sealable roll film	- Material stopper
- Single-layer PE	- Safety device
- Laminated film	- Bag support
Bag style	- PE sealing system
- Stand pillow bag	- Vacuum device
- Bag with hole	- Flip device
- Gusset bag	- Static eliminator
- Square bottom bag	- 4 lines folding device
- Chain bag	- Film tracking device
	- Special sealing jaws